




MBL

GALLERY

MBL LIGHT DUTY

Lintels above 1500mm must be propped.
For light duty applications e.g. meter boxes.



| Length | 750-900 | 1050-1350 | 1500-2100 |
|----------|---------|-----------|-----------|
| L (kN) | 2 | 4 | 5 |
| W (kg/m) | 2.3 | 2.9 | 4.1 |
| H (mm) | 52 | 87 | 92 |

(L) Load SWL (W) Weight (H) Height

PRODUCT ATTRIBUTES

| | |
|-----------------------------------|--|
| Brand | Birtley |
| Generic Ref | MBL |
| Product Range | Single Leaf External Walls |
| Product Type | Light Duty Meter Box Lintel - 100mm Brick |
| European Standard/ETA | BS EN845-2:2013+A1:2016 |
| Test Standard | EN846-9:2000/2016 |
| Notified Body | Lucideon Ltd (NB 1289) |
| Material | Mild Steel S275JR to BS EN10025-2:2004 |
| Coating/Finish/Colour | 65µm Hot Dip Galvanized to BS EN ISO 1461:2009 |
| Thermal Performance | Contact us for information |
| Fire Rating | 60 mins (with 2 coat plaster finish) |
| Installation requirement 1 | Bed fully on bricklaying mortar |
| Installation requirement 2 | Must be used with a cavity tray - External walls only |
| Installation requirement 3 | Lintels over 1500mm must be propped until masonry is fully loaded and cured. |
| Sales Qty | 1 |
| Packaging weight | 0 |
| Features/Benefits 1 | Supergalv coating offers superior life expectancy |

| | |
|----------------------------|---|
| Features/Benefits 2 | Post-fabrication galvanizing leaves no surface with inferior paint protection |
| Features/Benefits 3 | Structural grade steel to EN10025 |
| Options 1 | Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304) |