




OB190

GALLERY

OB190

STANDARD DUTY

Inner and outer leaves must be suitably tied.



Length	750-1500	1650-2100	2250-3000
L (kN)	9	12	20
W (kg/m)	5.8	8.2	11.4
H (mm)	87	92	157

PRODUCT ATTRIBUTES

Brand	Birtley
Generic Ref	OB190
Product Range	Solid Wall Lintels
Product Type	Standard Duty Solid Wall Lintel 200-215mm Wall
European Standard/ETA	BS EN845-2:2013+A1:2016
Test Standard	EN846-9:2000/2016
Notified Body	Lucideon Ltd (NB 1289)
Material	Mild Steel S275JR to BS EN10025-2:2004
Coating/Finish/Colour	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
Thermal Performance	Contact us for information
Fire Rating	60 mins (with 2 coat plaster finish)
Installation requirement 1	Bed fully on bricklaying mortar
Installation requirement 2	Must be used with a cavity tray - External walls only
Sales Qty	1
Packaging weight	0
Features/Benefits 1	Supergalv coating offers superior life expectancy
Features/Benefits 2	Post-fabrication galvanizing leaves no surface with inferior paint protection
Features/Benefits 3	Structural grade steel to EN10025

Options 1	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
Options 2	Outer Leaf Options: Render mesh (FM)