




## SBL200

### GALLERY

#### SBL200

##### MEDIUM DUTY

Inner and outer leaves must be suitably tied.



Length	750-1800	1950-2700	2850-3000	3150-3600	3750-4500
L (kN)	20	20	25	40	35
W (kg/m)	9.8	9.8	16.5	16.5	16.5
H (mm)	140	140	222	222	222

### PRODUCT ATTRIBUTES

<b>Brand</b>	Birtley
<b>Generic Ref</b>	SBL200
<b>Product Range</b>	Solid Wall Lintels
<b>Product Type</b>	Standard Duty Solid Wall Lintel 200-215mm Wall
<b>European Standard/ETA</b>	BS EN845-2:2013+A1:2016
<b>Test Standard</b>	EN846-9:2000/2016
<b>Notified Body</b>	Lucideon Ltd (NB 1289)
<b>Material</b>	Mild Steel S275JR to BS EN10025-2:2004
<b>Coating/Finish/Colour</b>	65µm Hot Dip Galvanized to BS EN ISO 1461:2009
<b>Thermal Performance</b>	Contact us for information
<b>Insulation</b>	OPTIONAL - Expanded Polystyrene - BREEAM rating A+
<b>Fire Rating</b>	60 mins (with 2 coat plaster finish)
<b>Installation requirement 1</b>	Bed fully on bricklaying mortar
<b>Installation requirement 2</b>	Must be used with a cavity tray - External walls only
<b>Sales Qty</b>	1
<b>Packaging weight</b>	0
<b>Features/Benefits 1</b>	Supergalv coating offers superior life expectancy
<b>Features/Benefits 2</b>	Post-fabrication galvanizing leaves no surface with inferior paint

	protection
<b>Features/Benefits 3</b>	Structural grade steel to EN10025
<b>Options 1</b>	Alternative material options: Ultragalv coating (150µm), Stainless Steel 1.4301 (304)
<b>Options 2</b>	Outer Leaf Options: No rainwater drip (ND), Render mesh (MF)
<b>Options 3</b>	Add Insulation (INS)